## NSN 5305-01-183-5876

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-183-5876 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 1.323 inches and 1.353 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.376 inches and 0.385 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Unthreaded Hole Diameter:** 0.070 inches first hole and 0.075 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.200 inches first hole and 1.240 inches first hole Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-183-5876

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0