

View Online at <https://aerobasegroup.com/nsn/5305-01-183-8722>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.418 inches and 0.500 inches

**Fastener Length:**

Between 0.480 inches and 0.500 inches

**Head Style:**

Watertight

**Head Diameter:**

Between 0.256 inches and 0.294 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**Locking Feature:**

Strip threads or patch threads or pellet threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Special Features:**

Furnished with one o-ring

**Material:**

Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

**Material Specification:**

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or astm a493 assn standard 1st material response or astm a493 assn standard 2nd material response or astm a493 assn standard 3rd material response or astm a493 assn standard 4th material response or astm a493 assn standard 5th material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0