## NSN 5305-01-183-9269

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-183-9269

| Thread Class:   |  |
|---|--|
| 3a  |  |
| Thread Direction:   |  |
| Right-hand  |  |
| Head Style:   |  |
| Flat chamfer  |  |
| Head Diameter:  |  |
| Between 0.262 inches and 0.270 inches                                 |  |
| Head Height:  |  |
| Between 0.159 inches and 0.164 inches                                 |  |
| Internal Drive Style:   |  |
| Hexagon   |  |
| Material Accommodated Thickness:                                      |  |
| Between 0.032 inches and 0.093 inches                                 |  |
| Thread Diameter:  |  |
| 0.164 inches  |  |
| Width Across Flats:   |  |
| 0.141 inches  |  |
| Thready Qty Per Inch (tpi):   |  |
| 32  |  |
| Special Features:   |  |
| Straight knurl head   |  |
| Material:   |  |
| Steel comp 302 spring   |  |
| Material Specification:   |  |
| Qq-w-423 cond a federal specification single material response spring |  |
| Surface Treatment:  |  |
| Passivate spring  |  |
| Surface Treatment Specification:                                      |  |
| Qq-p-35 federal specification single treatment response spring        |  |
| Thread Series Designator:   |  |
| Unc   |  |
| Shelf Life:   |  |
| N/a   |  |
| Unit Of Measure:  |  |
|   |  |
| Demilitarization:   |  |
| No  |  |
| Fiig:   |  |
| A003b0  |  |
| Mil-std (military Standard):  |  |
| Mil-s-5059 spec.  |  |
|   |  |