## NSN 5305-01-184-3517

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-184-3517 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.650 inches and 0.700 inches **Fastener Length:** Between 1.535 inches and 1.565 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.8260 inches and 0.8884 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.4375 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Titanium alloy **Material Specification:** Ams 4967, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-01-184-3517

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0