

View Online at <https://aerobasegroup.com/nsn/5305-01-185-0570>

Thread Class:

2a

Thread Direction:

Right-hand

Fastener Length:

Between 0.677 inches and 0.697 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.262 inches and 0.270 inches

Head Height:

Between 0.159 inches and 0.164 inches

Point Length:

0.100 inches

Point Diameter:

Between 0.116 inches and 0.121 inches

Point Style:

Flat

Internal Drive Style:

Hexagon

Thread Diameter:

0.164 inches

Width Across Flats:

Between 0.141 inches and 0.143 inches

Thready Qty Per Inch (tpi):

32

Point Chamfer Angle:

270.0 degrees

Special Features:

Color black. Two key ways on threads 0.040 min diameter 0.050 maximum dia

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

Qq-s-763 federal specification all material responses

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, cl 4 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.