## NSN 5305-01-185-2212



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-185-2212 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** Between 0.765 inches and 0.812 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.502 inches and 0.507 inches **Shoulder Diameter:** 0.280 inches first shoulder and 0.281 inches first shoulder **Shoulder Length:** 0.302 inches first shoulder and 0.322 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one o ring. Must be lubricated with cetyl alcohol Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf

N/a Unit Of Measure:

Shelf Life:

## NSN 5305-01-185-2212

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0