

View Online at <https://aerobasegroup.com/nsn/5305-01-185-3341>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.886 inches and 1.000 inches

Fastener Length:

Between 0.969 inches and 1.000 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

80000 pounds per square inch

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 or steel comp 303 plus x or steel comp 303ma or steel comp 303cu

Screw Material Specification:

66 assn standard all material responses

Screw Surface Treatment:

Paint

Screw Surface Treatment Specification:

Mil-e-15090 type 3 cl 2 military specification single treatment response

Special Features:

Color gray two coats; primer one coat per mil-p-15328; second primer one coat color y per tt-p-1757

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-e-15090 spec.