NSN 5305-01-185-4643

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-185-4643

Thread Class:3aThread Direction:Right-handThread Length:Between 0.378 inches and 0.428 inchesFastener Length:Between 0.826 inches and 0.856 inchesHead Style:Flat countersunkHead Diameter:Between 0.464 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThread Via Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material responseThread Series Designator:
Thread Direction: Right-hand Thread Length: Between 0.378 inches and 0.428 inches Fastener Length: Between 0.826 inches and 0.856 inches Head Style: Flat countersunk Head Diameter: Between 0.464 inches and 0.507 inches Grip Diameter: Between 0.490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Ams4967, comp 6al-4v assn standard single material response
Right-hand Thread Length: Between 0.378 inches and 0.428 inches Fastener Length: Between 0.826 inches and 0.856 inches Head Style: Flat countersunk Head Diameter: Between 0.464 inches and 0.507 inches Grip Diameter: Between 0.2490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Thread Length: Between 0.378 inches and 0.428 inches Fastener Length: Between 0.826 inches and 0.856 inches Head Style: Flat countersunk Head Diameter: Between 0.464 inches and 0.507 inches Grip Diameter: Between 0.2490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 0.428 inches and 0.448 inches Thread Y Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Between 0.378 inches and 0.428 inches Fastener Length: Between 0.826 inches and 0.856 inches Head Style: Flat countersunk Head Diameter: Between 0.464 inches and 0.507 inches Grip Diameter: Between 0.2490 inches and 0.2495 inches Internal Drive Style: High-torque Thread Diameter: 0.250 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Fastener Length:Between 0.826 inches and 0.856 inchesHead Style:Flat countersunkHead Diameter:Between 0.464 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
Between 0.826 inches and 0.856 inchesHead Style:Flat countersunkHead Diameter:Between 0.464 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
Head Style:Flat countersunkHead Diameter:Between 0.464 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
Flat countersunkHead Diameter:Between 0.464 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 9.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
Head Diameter:Between 0.464 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
Between 0.464 inches and 0.507 inchesGrip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
Grip Diameter:Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
Between 0.2490 inches and 0.2495 inchesInternal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
Internal Drive Style:High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
High-torqueThread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
Thread Diameter:0.250 inchesGrip Length:Between 0.428 inches and 0.448 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
0.250 inches Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Thready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesSurface Finish:32.0 microinches threadsMaterial:Titanium alloyMaterial Specification:Ams4967, comp 6al-4v assn standard single material response
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Surface Finish: 32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
32.0 microinches threads Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Material: Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Titanium alloy Material Specification: Ams4967, comp 6al-4v assn standard single material response
Material Specification: Ams4967, comp 6al-4v assn standard single material response
Ams4967, comp 6al-4v assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-185-4643

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

