NSN 5305-01-185-7069

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-185-7069 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.434 inches and 0.531 inches **Fastener Length:** Between 0.484 inches and 0.531 inches **Head Style:** Hexagon **Head Height:** Between 0.049 inches and 0.060 inches Width Between Flats: Between 0.181 inches and 0.189 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Mrap rg-33 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1802 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-185-7069

Machine Screw - Page 2 of 2



Fiig:

A500d0