

View Online at <https://aerobasegroup.com/nsn/5305-01-185-7121>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.750 inches and 0.938 inches

Fastener Length:

Between 4.906 inches and 5.000 inches

Head Style:

Hexagon

Head Height:

Between 0.150 inches and 0.163 inches

Width Between Flats:

Between 0.4280 inches and 0.4375 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell c

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0