NSN 5305-01-185-7125

Shoulder Screw - Page 1 of 2

Thread Class:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5305-01-185-7125

Right-hand
Thread Length:
Between 0.443 inches and 0.510 inches
Fastener Length:
Between 0.828 inches and 0.875 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.456 inches and 0.508 inches
Head Height:
Between 0.058 inches and 0.060 inches
Shoulder Diameter:
0.2802 inches first shoulder and 0.2807 inches first shoulder
Shoulder Length:
0.307 inches first shoulder and 0.325 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Special Features:
Furnished with one o ring
Furnished with one o ring Material:
•
Material:
Material: Steel comp xm-13
Material: Steel comp xm-13 Material Specification:
Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response
Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment:
Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate
Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response

NSN 5305-01-185-7125

Shoulder Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0