## NSN 5305-01-185-7134

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-185-7134 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.650 inches and 0.700 inches **Fastener Length:** Between 1.848 inches and 1.878 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.826 inches and 0.888 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.178 inches and 1.198 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Titanium alloy **Material Specification:** Ams4967, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-185-7134

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0