Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-185-8666



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.371 inches and 0.437 inches

Fastener Length:

Between 0.407 inches and 0.437 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.134 inches and 0.140 inches

Head Height:

Between 0.083 inches and 0.086 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.086 inches

Width Across Flats:

Between 0.0781 inches and 0.0791 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell c

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty1, cl2 federal specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-185-8666

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

