## NSN 5305-01-185-8667



Socket Head Cap Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-185-8667 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.318 inches and 0.358 inches **Fastener Length:** Between 0.865 inches and 0.885 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.157 inches and 0.159 inches Thready Qty Per Inch (tpi): 32 **Special Features:** Provided with two keyways180 degrees apart 0.785 in. Min by 0.805 in. Maximum Ig by 0.049 in. Nom width by 0.078 in. Depth and half dog point .100 in. Lg Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 384 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:**