Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-186-0626

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.110 incl	ues and 0.140 inches
Fastener Length:	
Between 0.370 incl	ies and 0.380 inches
Head Style:	
Pan	
Head Diameter:	
Between 0.205 inch	nes and 0.219 inches
Head Height:	
Between 0.070 incl	nes and 0.080 inches
First Diameter Fro	m Head:
Between 0.070 incl	nes and 0.080 inches
Distance From La	gest Bearing Surface Of Head To End Of First Diameter:
Between 0.240 incl	ies and 0.260 inches
Internal Drive Styl	e:
Cross recess type	
Thread Diameter:	
0.112 inches	
Thready Qty Per In	nch (tpi):
40	
Externally Relieve	d Body Diameter Quantity:
1	
Material:	
Steel comp 302 or	steel comp 304 or steel comp 3041 or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel
comp 316l or steel	comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347
Material Specifica	tion:
Qq-s-763 federal s	pecification all material responses
Surface Treatmen	
Passivate	
Surface Treatmen	t Specification:
Qq-p-35 federal sp	ecification single treatment response
Thread Series Des	ignator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 5305-01-186-0626

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

