NSN 5305-01-186-0662

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-186-0662

Thread Cla	ISS:
3a	
Thread Dir	ection:
Right-hand	
Thread Le	ngth:
Between 0.	338 inches and 0.388 inches
Fastener L	ength:
Between 1.	098 inches and 1.128 inches
Head Style	
Pan no. 2	
Head Diam	eter:
Between 0.	360 inches and 0.374 inches
Head Heig	ht:
Between 0.	115 inches and 0.125 inches
Grip Diam	eter:
Between 0.	1885 inches and 0.1895 inches
Internal Dr	ive Style:
Offset cruc	form (torque set)
Thread Dia	imeter:
0.190 inche	es
Grip Leng	h:
Between 0.	740 inches and 0.760 inches
Thready Q	ty Per Inch (tpi):
32	
Min. Tensi	le Strength (psi):
160000 po	unds per square inch
Surface Fi	nish:
32.0 microi	nches threads
Special Fe	atures:
Internal driv	ve ribbed
Material:	
Iron alloy 6	60
Material S	pecification:
Ams5731 a	ssn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material res	sponse
Surface Tr	eatment:
Passivate	
Surface Tr	eatment Specification:
Qq-p-35 fe	deral specification single treatment response
Thread Se	ries Designator:
Unjf	
Specificati	on Data:
80205-nas	1578 professional/industrial association standard

NSN 5305-01-186-0662

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

