

View Online at <https://aerobasegroup.com/nsn/5305-01-186-2167>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.238 inches

**Fastener Length:**

Between 0.348 inches and 0.378 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.226 inches

**Grip Diameter:**

Between 0.1105 inches and 0.1115 inches

**Internal Drive Style:**

Tri-wing recess

**Thread Diameter:**

0.112 inches

**Grip Length:**

Between 0.115 inches and 0.135 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416a, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas4400 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.