NSN 5305-01-186-3440

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-186-3440 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.290 inches and 0.330 inches **Fastener Length:** Between 0.550 inches and 0.570 inches **Head Style:** Flat countersunk undercut **Head Diameter:** 0.279 inches **Head Height:** 0.060 inches **First Diameter From Head:** Between 0.088 inches and 0.098 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.240 inches and 0.260 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Countersink Angle:** 100.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-186-3440

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0