NSN 5305-01-186-3452

Shoulder Screw - Page 1 of 2

3a

28

N/a





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.443 inches and 0.510 inches Fastener Length: Between 1.391 inches and 1.438 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.456 inches and 0.508 inches **Head Height:** Between 0.582 inches and 0.602 inches **Shoulder Diameter:** 0.2802 inches first shoulder and 0.2807 inches first shoulder Shoulder Length: 0.868 inches first shoulder and 0.890 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.281 inches Thready Qty Per Inch (tpi): **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Furnished with one o ring Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

NSN 5305-01-186-3452

Shoulder Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

