NSN 5305-01-186-7693

Close Tolerance Screw - Page 1 of 2

3a





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.306 inches and 0.357 inches Fastener Length: Between 1.040 inches and 1.060 inches **Head Style:** Crowned hexagon **Head Height:** Between 0.157 inches and 0.172 inches Width Between Flats: Between 0.492 inches and 0.502 inches Locking Feature: Detent ball grip **Grip Diameter:** Between 0.3112 inches and 0.3117 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Grip Length: Between 0.562 inches and 0.578 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 0.087 inches first hole and 0.123 inches first hole Surface Finish: 32.0 microinches grip Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

24

NSN 5305-01-186-7693

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

