

View Online at <https://aerobasegroup.com/nsn/5305-01-186-8622>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.378 inches and 0.428 inches

**Fastener Length:**

Between 1.576 inches and 1.606 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.477 inches and 0.492 inches

**Head Height:**

Between 0.140 inches and 0.150 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.178 inches and 1.198 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Internal drive ribbed

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1578 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0