

View Online at <https://aerobasegroup.com/nsn/5305-01-186-9265>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.214 inches and 0.250 inches

**Fastener Length:**

0.250 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.124 inches and 0.140 inches

**Head Height:**

Between 0.053 inches and 0.062 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.086 inches

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Screw Material:**

Steel comp 202 or steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 304 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 420 or steel comp 430 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 446

**Screw Material Specification:**

Qq-s-763 federal specification all material responses

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

3608009 fscm 27914 mfr ref single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0