

View Online at <https://aerobasegroup.com/nsn/5305-01-186-9286>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.515 inches and 0.555 inches

Fastener Length:

Between 1.463 inches and 1.483 inches

Head Style:

Flat countersunk

Head Diameter:

0.508 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Grip Length:

Between 0.928 inches and 0.948 inches

Width Across Flats:

Between 0.1565 inches and 0.1587 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

100.0 degrees

Surface Finish:

32.0 microinches threads

Special Features:

3 keyways 1.317 in. Min. And 1.347 in. Maximum long, 0.040 in. Min and 0.044 in. Maximum wide machined in shank, bore machined in thread end to receive plug

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0