NSN 5305-01-187-3468

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-187-3468 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.280 inches and 0.340 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.3030 inches and 0.3125 inches **Head Height:** Between 0.185 inches and 0.190 inches **First Diameter From Head:** Between 0.130 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.629 inches and 0.720 inches **Point Style:** Flat **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Thread Series Designator:**

Unf

NSN 5305-01-187-3468

Externally Relieved Body Screw - Page 2 of 2



| Shelf Life: | She | lf | Life: |
|-------------|-----|----|-------|
|-------------|-----|----|-------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0