

View Online at <https://aerobasegroup.com/nsn/5305-01-187-5838>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.425 inches and 0.465 inches

Fastener Length:

Between 0.810 inches and 0.830 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.360 inches and 0.374 inches

Head Height:

Between 0.125 inches and 0.135 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Width Across Flats:

Between 0.125 inches and 0.127 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Surface Finish:

32.0 microinches threads

Special Features:

3 keyways 0.780 in. Min. And 0.800 in. Max. Long and 0.030 inch min. And 0.034 inch max. Wide machined in shank. Bore machined in thread end to receive plug

Material:

Iron alloy 660

Material Specification:

Ams 5732 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0