

View Online at <https://aerobasegroup.com/nsn/5305-01-187-5958>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.364 inches and 0.414 inches

**Fastener Length:**

Between 0.562 inches and 0.592 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.435 inches and 0.510 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Single Shear Strength:**

95000 pounds per square inch

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.178 inches and 0.198 inches

**Thread Qty Per Inch (tpi):**

28

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5737 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0