
Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-187-6061



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.231 inches and 0.312 inches
Fastener Length:
Between 0.281 inches and 0.312 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.177 inches and 0.225 inches
Locking Feature:
Strip threads or patch threads or pellet threads
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification all treatment responses
Thread Series Designator:
Unjc
Specification Data:
80205-nas1189 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-187-6061

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

