

View Online at <https://aerobasegroup.com/nsn/5305-01-187-6083>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.277 inches and 0.328 inches

**Fastener Length:**

Between 2.918 inches and 2.938 inches

**Head Style:**

Crowned hexagon

**Head Height:**

Between 0.126 inches and 0.141 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Locking Feature:**

Detent ring grip

**Grip Diameter:**

Between 0.2487 inches and 0.2492 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 2.500 inches and 2.516 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

63000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.119 inches first hole and 0.155 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0