NSN 5305-01-188-7580

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-188-7580

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
1.750 inches	
Fastener Length:	
Between 2.359 inche	s and 2.406 inches
Head Style:	
Hexagon	
Head Height:	
Between 0.080 inche	s and 0.093 inches
Nidth Between Flat	S:
Between 0.243 inche	s and 0.251 inches
nternal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.138 inches	
Thready Qty Per Inc	h (tpi):
32	
Min. Tensile Strengt	h (psi):
160000 pounds per s	quare inch
lardness Rating:	
Between 36.0 rockwe	II c and 40.0 rockwell c
Screw Material:	
Steel comp e4340 or	steel comp 8740
Screw Material Spec	ification:
Vil-s-5000 military sp	ecification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard
2nd material respons	Э
Screw Surface Trea	ment:
Cadmium and chrom	ate
Screw Surface Trea	ment Specification:
Qq-p-416 ty2 cl2 fede	ral specification single treatment response
Thread Series Desig	nator:
Unjc	
Specification Data:	
80205-nas1801 profe	ssional/industrial association standard
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	

NSN 5305-01-188-7580

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-5000 spec.

