

View Online at <https://aerobasegroup.com/nsn/5305-01-188-9244>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.158 inches and 0.178 inches

Fastener Length:

Between 0.565 inches and 0.575 inches

Head Style:

Hexagon

Head Height:

Between 0.031 inches and 0.036 inches

Width Between Flats:

Between 0.367 inches and 0.375 inches

First Diameter From Head:

Between 0.140 inches and 0.150 inches

Second Diameter From Head:

Between 0.1555 inches and 0.1559 inches

Third Diameter From Head:

Between 0.095 inches and 0.100 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.040 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.350 inches and 0.360 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.397 inches and 0.407 inches

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

28.0 rockwell c and 35.0 rockwell c

Externally Relieved Body Diameter Quantity:

3

Special Features:

One center drill 0.070 each end optional

Material:

Steel comp 410

Material Specification:

Ams 5613 assn standard single material response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0