## NSN 5305-01-189-2797



Panel Screw Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-189-2797 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.188 inches and 0.218 inches **Fastener Length:** Between 0.271 inches and 0.301 inches **Head Style:** Pan **Head Diameter:** Between 0.250 inches and 0.280 inches **Head Height:** Between 0.077 inches and 0.107 inches **Material Accommodated Thickness:** Between 0.031 inches and 0.062 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: 45.0 rockwell c primary washer and 53.0 rockwell c primary washer **Product Name:** Navy special project **Special Features:** Finish color black **Material Specification:** Qq-s-763 federal specification single material response stand-off **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl3 military specification single treatment response **Thread Series Designator:** Unc

Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No

## NSN 5305-01-189-2797

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.