

View Online at <https://aerobasegroup.com/nsn/5305-01-189-3770>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.262 inches and 0.375 inches

**Fastener Length:**

Between 0.345 inches and 0.375 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.303 inches and 0.313 inches

**Head Height:**

Between 0.185 inches and 0.190 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.1562 inches and 0.1587 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell c

**Minimum Yield Strength:**

30000 pounds per square inch

**Special Features:**

Knurling optional

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

6 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.