NSN 5305-01-189-7400

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-189-7400

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.150 inches
Fastener Length:
0.580 inches
Head Style:
Flat countersunk undercut
Head Diameter:
0.332 inches
Head Height:
0.072 inches
First Diameter From Head:
0.120 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.358 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Externally Relieved Body Diameter Quantity:
1
Special Features:
Color black
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
66 federal standard all material responses
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924, class 2 military specification single treatment response
Thread Series Designator:

Unc

NSN 5305-01-189-7400

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-13924 spec.