## NSN 5305-01-190-0247

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-190-0247

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.556 inches and 0.616 inches
Fastener Length:
Between 1.401 inches and 1.421 inches
Head Style:
Oval countersunk
Head Diameter:
Between 0.355 inches and 0.397 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Width Across Flats:
Between 0.1565 inches and 0.1587 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
100.0 degrees
Surface Finish:
32.0 microinches threads
Special Features:
3 keyways 120 degreesapart, thd end drilled, counterbored and reamed for plug
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Linif

## NSN 5305-01-190-0247

Close Tolerance Screw - Page 2 of 2



		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0