NSN 5305-01-190-0250

Close Tolerance Screw - Page 1 of 2

3a





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.425 inches and 0.465 inches Fastener Length: Between 0.747 inches and 0.767 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.264 inches and 0.303 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Grip Length: Between 0.302 inches and 0.322 inches Width Across Flats: Between 0.1253 inches and 0.1270 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees Surface Finish: 32.0 microinches threads **Special Features:** 3 keyways 120 degreesapart. Thd. End drilled, counterbored and reamed for plug Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

32

NSN 5305-01-190-0250

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

