NSN 5305-01-190-0252

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-190-0252

3aThread Direction:Right-handThread Length:0.403 inchesFastener Length:Between 1.388 inches and 1.418 inchesHead Style:Flat countersunkHead Diameter:Between 0.464 inches and 0.506 inchesGrip Diameter:Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Arns 5731 assn standard single material responseSurface Treatment:Cadmium
Right-handThread Length:0.403 inchesFastener Length:Between 1.388 inches and 1.418 inchesHead Style:Flat countersunkHead Diameter:Between 0.464 inches and 0.506 inchesGrip Diameter:Between 0.485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Arns 5731 assn standard single material responseSurface Treatment:Cadmium
Tread Length:0.403 inchesFastener Length:Between 1.388 inches and 1.418 inchesHead Style:Flat countersunkHead Diameter:Between 0.464 inches and 0.506 inchesGrip Diameter:Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Arms 5731 assn standard single material responseCadmium
0.403 inches Fastener Length: Between 1.388 inches and 1.418 inches Head Style: Flat countersunk Head Diameter: Between 0.464 inches and 0.506 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.250 inches Grip Length: Between 0.900 inches and 1.010 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Cadmium
Fastener Length:Between 1.388 inches and 1.418 inchesHead Style:Flat countersunkHead Diameter:Between 0.464 inches and 0.506 inchesGrip Diameter:Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Arns 5731 assn standard single material responseSurface Treatment:Cadmium
Between 1.388 inches and 1.418 inchesHead Style:Flat countersunkHead Diameter:Between 0.464 inches and 0.506 inchesGrip Diameter:Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Arns 5731 assn standard single material responseSurface Treatment:Cadmium
Head Style:Flat countersunkHead Diameter:Between 0.464 inches and 0.506 inchesGrip Diameter:Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Arms 5731 assn standard single material responseSurface Treatment:Cadmium
Flat countersunkHead Diameter:Between 0.464 inches and 0.506 inchesGrip Diameter:Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Arns 5731 assn standard single material responseSurface Treatment:Cadmium
Head Diameter:Between 0.464 inches and 0.506 inchesGrip Diameter:Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material responseSurface Treatment:Cadmium
Between 0.464 inches and 0.506 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.250 inches Grip Length: Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
Grip Diameter:Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material responseSurface Treatment:Cadmium
Between 0.2485 inches and 0.2495 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material responseSurface Treatment:Cadmium
Internal Drive Style:Offset cruciform (torque set)Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material responseSurface Treatment:Cadmium
Offset cruciform (torque set) Thread Diameter: 0.250 inches Grip Length: Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
Thread Diameter:0.250 inchesGrip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material responseSurface Treatment:Cadmium
0.250 inches Grip Length: Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
Grip Length:Between 0.990 inches and 1.010 inchesThready Qty Per Inch (tpi):28Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material responseSurface Treatment:Cadmium
Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
28 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
Min. Tensile Strength (psi):160000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material responseSurface Treatment:Cadmium
160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Surface Treatment: Cadmium
Material Specification:Ams 5731 assn standard single material responseSurface Treatment:Cadmium
Ams 5731 assn standard single material response Surface Treatment: Cadmium
Surface Treatment: Cadmium
Cadmium
Surface Treatment Specification:
•
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-190-0252

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

