# NSN 5305-01-190-2192

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-190-2192



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.214 inches and 0.307 inches

#### Fastener Length:

Between 0.344 inches and 0.375 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.319 inches and 0.332 inches

#### Internal Drive Style:

Torque set

#### **Thread Diameter:**

0.164 inches

### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

#### Countersink Angle:

Between 99.0 degrees and 101.0 degrees

#### Screw Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

#### **Screw Surface Treatment:**

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

#### **Special Features:**

Internal drive ribbed

#### **Thread Series Designator:**

Unjc

## **Specification Data:**

80205-nas1102 professional/industrial association standard

### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5305-01-190-2192

Machine Screw - Page 2 of 2

Fiig: A500d0

