

View Online at <https://aerobasegroup.com/nsn/5305-01-190-4559>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.686 inches and 0.750 inches

Fastener Length:

Between 1.140 inches and 1.172 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.805 inches and 0.890 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.438 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 8740 or steel comp 8630

Screw Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-6049 spec.