NSN 5305-01-190-4569

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-190-4569 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.281 inches and 0.375 inches **Fastener Length:** Between 0.343 inches and 0.375 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch **Hardness Rating:** 45.0 rockwell c secondary washer and 53.0 rockwell c secondary washer Secondary Washer Relationship To Primary Washer: Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.293 inches **Secondary Washer Outside Diameter:** Between 0.307 inches and 0.317 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.040 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches

Material:

Steel

NSN 5305-01-190-4569

Assembled Washer Screw - Page 2 of 2



Material Specification:
Qq-s-633 federal specification single material response fastene
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Specification Data:
80205-nas1301 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A003b0