NSN 5305-01-190-4570

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-190-4570

View Online at https://aerobasegroup.com/nsn/5305-01-190-4570
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.230 inches and 0.312 inches
Fastener Length:
Between 0.280 inches and 0.312 inches
Head Style:
Pan
Head Diameter:
Between 0.205 inches and 0.219 inches
Head Height:
Between 0.078 inches and 0.080 inches
Washer Quantity:
2
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
55000 pounds per square inch
Hardness Rating:
45.0 rockwell c secondary washer and 53.0 rockwell c secondary washer
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
0.172 inches
Secondary Washer Outside Diameter:
Between 0.213 inches and 0.223 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
0.025 inches
Secondary Washer Material Thickness:
Between 0.013 inches and 0.019 inches
Material Specification:

Qq-s-633 federal specification single material response fastener

NSN 5305-01-190-4570

Assembled Washer Screw - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Specification Data:
80205-nas1301 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A003b0