## NSN 5305-01-190-4591

Close Tolerance Screw - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/5305-01-190-4591

| 3a         Thread Direction:         Right-hand         Thread Length:         Between 0.364 inches and 0.414 inches         Fastener Length:         Between 1.749 inches and 1.779 inches         Head Siyle:         Flat countersunk         Head Direction:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.455 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thread Yay Per Inch (tpi):         28         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         3.2.0 microinches threads         Material:         Non alloy 660         Material:         Condiction:         Ams5737 assn standard single material response         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification:         Cap-p-416, ty2, cl2 federal specification single treatment response         Thread Series Designator:         Unjf         <  | 3a         Thread Direction:         Right-hand         Thread Length:         Between 0.364 inches and 0.414 inches         Fastener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.485 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron alloy 660         Material Specification:         Cadmium and chromate         Surface Treatment Specification         Gurier Inset Designator:         Urif         Shelf Life:         Na         Unif         Date Si Designator:         Unif   |  |
|--|--|--|
| Thread Direction:         Right-hand         Thread Length:         Between 0.364 inches and 0.414 inches         Fastener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.455 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Diameter:         0.250 inches         Gross recess type 1         Thread Paimeter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron aloy 660         Material Specification:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Chread Series Designator:         Unjf         Shelf Life: <td>Thread Direction:         Right-hand         Thread Length:         Between 0.364 inches and 0.414 inches         Fastener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.455 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Diameter:         0.250 inches         Gross recess type 1         Thread Paimeter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron aloy 660         Material Specification:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Chread Series Designator:         Unjf         Shelf Life:<td>Thread Class:</td></td> | Thread Direction:         Right-hand         Thread Length:         Between 0.364 inches and 0.414 inches         Fastener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.455 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Diameter:         0.250 inches         Gross recess type 1         Thread Paimeter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron aloy 660         Material Specification:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Chread Series Designator:         Unjf         Shelf Life: <td>Thread Class:</td>                                | Thread Class:                                  |
| Right-hand         Right-hand         Pread Length:         Between 0.364 inches and 0.414 inches         Fastener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.455 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron aloy 660         Material Specification:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Chread Series Designator:         Unjf         Sheft Life:         N/a         Unif         Sheft Life:         N/a         Designator:  | Right-hand         Right-hand         Pread Length:         Between 0.364 inches and 0.414 inches         Fastener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.455 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron aloy 660         Material Specification:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Chread Series Designator:         Unjf         Sheft Life:         N/a         Unif         Sheft Life:         N/a         Designator:  |  |
| Thread Length:         Between 0.364 inches and 0.414 inches         Fastener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.4285 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Day Per Inch (tpi):         28         Contersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material         Protad Style:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification:         Cadp-p-416, ty2, cl2 federal specification single treatment response         Thread Series Designator:         Unjf         Sheff Life:         N/a         Destrict Destriction:         Unif         Destrict Destyles         Destrict Destyles  | Thread Length:         Between 0.364 inches and 0.414 inches         Fastener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.4285 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Day Per Inch (tpi):         28         Contersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material         Protad Style:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification:         Cadp-p-416, ty2, cl2 federal specification single treatment response         Thread Series Designator:         Unjf         Sheff Life:         N/a         Destrict Destriction:         Unif         Destrict Destyles         Destrict Destyles                          |  |
| Astener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.455 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material         Ion alloy 660         Material Specification:         Aums5737 assn standard single material response         Surface Treatment         Cadmium and chromate         Surface Treatment Specification:         Qu-p-116, ty2, cl2 federal specification single treatment response         Thread Series Designator:         Unjf         Shelf Life:         N/a         Date Treatment:         Combium and chromate         Surface Treatment Specification single treatment response         Thread   | Astener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.455 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 9.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material         Ion alloy 660         Material Specification:         Aums5737 assn standard single material response         Surface Treatment         Cadmium and chromate         Surface Treatment Specification:         Qu-p-116, ty2, cl2 federal specification single treatment response         Thread Series Designator:         Unjf         Shelf Life:         N/a         Date Treatment:         Combium and chromate         Surface Treatment Specification single treatment response         Thread | -  |
| Fastener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron alloy 660         Material Specification:         Ams5737 assn standard single material response         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification single treatment response         Thread Series Designator:         Unjf         Shelf Life:         N/a         Unit Of Measure:         -  | Fastener Length:         Between 1.749 inches and 1.779 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron alloy 660         Material Specification:         Ams5737 assn standard single material response         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification single treatment response         Thread Series Designator:         Unjf         Shelf Life:         N/a         Unit Of Measure:         -                                | -  |
| Between 1.749 inchess         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inchess         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron alloy 660         Material Specification:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification single treatment response         Chread Series Designator:         Unjf         Shelf Life:         N/a         Unit Of Measure:         Tread         Parentiltarization:   | Between 1.749 inchess         Head Style:         Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inchess         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron alloy 660         Material Specification:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification single treatment response         Chread Series Designator:         Unjf         Shelf Life:         N/a         Unit Of Measure:         Tread         Parentiltarization:   |  |
| Head Style:<br>Flat countersunk<br>Head Diameter:<br>Between 0.455 inches and 0.510 inches<br>Grip Diameter:<br>Between 0.2485 inches and 0.2495 inches<br>Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment:<br>Qa-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Head Style:<br>Flat countersunk<br>Head Diameter:<br>Between 0.455 inches and 0.510 inches<br>Grip Diameter:<br>Between 0.2485 inches and 0.2495 inches<br>Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment:<br>Qa-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | -  |
| Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron alloy 660         Material Specification:         Ams5737 assn standard single material response         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification single treatment response         Thread Series Designator:         Unjf         Shelf Life:         N/a         Unif Measure:         Iro         Pael Life Measure:         Iro         Bernellitarization:  | Flat countersunk         Head Diameter:         Between 0.455 inches and 0.510 inches         Grip Diameter:         Between 0.2485 inches and 0.2495 inches         Internal Drive Style:         Cross recess type 1         Thread Diameter:         0.250 inches         Grip Length:         Between 1.365 inches and 1.385 inches         Thready Qty Per Inch (tpi):         28         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Surface Finish:         32.0 microinches threads         Material:         Iron alloy 660         Material Specification:         Ams5737 assn standard single material response         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification single treatment response         Thread Series Designator:         Unjf         Shelf Life:         N/a         Unif Measure:         Iro         Pael Life Measure:         Iro         Bernellitarization:  | Between 1.749 inches and 1.779 inches          |
| Head Diameter:<br>Between 0.455 inches and 0.510 inches<br>Grip Diameter:<br>Between 0.2485 inches and 0.2495 inches<br>Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment:<br>Q-q-P.416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unif of Measure:<br>  | Head Diameter:<br>Between 0.455 inches and 0.510 inches<br>Grip Diameter:<br>Between 0.2485 inches and 0.2495 inches<br>Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment:<br>Q-q-P.416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unif of Measure:<br>  | Head Style:                                    |
| Between 0.455 inches and 0.510 inches<br>Grip Diameter:<br>Between 0.2485 inches and 0.2495 inches<br>Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 asen standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Between 0.455 inches and 0.510 inches<br>Grip Diameter:<br>Between 0.2485 inches and 0.2495 inches<br>Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 asen standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Flat countersunk                               |
| Grip Diameter:<br>Between 0.2485 inches and 0.2495 inches<br>Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Grip Diameter:<br>Between 0.2485 inches and 0.2495 inches<br>Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Head Diameter:                                 |
| Between 0.2485 inches and 0.2495 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Grip Length: Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Cadmium and chromate Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:  | Between 0.2485 inches and 0.2495 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.250 inches Grip Length: Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 28 Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Cadmium and chromate Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:  | Between 0.455 inches and 0.510 inches          |
| Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | Internal Drive Style:<br>Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | Grip Diameter:                                 |
| Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Cross recess type 1<br>Thread Diameter:<br>0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Between 0.2485 inches and 0.2495 inches        |
| Thread Diameter:   0.250 inches   Grip Length:   Between 1.365 inches and 1.385 inches   Thready Qty Per Inch (tpi):   28   Countersink Angle:   Between 99.0 degrees and 101.0 degrees   Surface Finish:   32.0 microinches threads   Material:   Iron alloy 660   Material Specification:   Ams5737 assn standard single material response   Surface Treatment:   Cadmium and chromate   Surface Treatment Specification single treatment response   Thread Series Designator:   Unjf   Shelf Life:   N/a   Unit Of Measure:   -   -   Demilitarization:   | Thread Diameter:   0.250 inches   Grip Length:   Between 1.365 inches and 1.385 inches   Thready Qty Per Inch (tpi):   28   Countersink Angle:   Between 99.0 degrees and 101.0 degrees   Surface Finish:   32.0 microinches threads   Material:   Iron alloy 660   Material Specification:   Ams5737 assn standard single material response   Surface Treatment:   Cadmium and chromate   Surface Treatment Specification single treatment response   Thread Series Designator:   Unjf   Shelf Life:   N/a   Unit Of Measure:   -   -   Demilitarization:   | Internal Drive Style:                          |
| 0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Arns5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | 0.250 inches<br>Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Arns5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | Cross recess type 1                            |
| Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Grip Length:<br>Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Thread Diameter:                               |
| Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>-<br>Demilitarization:  | Between 1.365 inches and 1.385 inches<br>Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>-<br>Demilitarization:  | 0.250 inches                                   |
| Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unif<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | Thready Qty Per Inch (tpi):<br>28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unif<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | Grip Length:                                   |
| 28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | 28<br>Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>  | Between 1.365 inches and 1.385 inches          |
| Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Countersink Angle:<br>Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Thready Qty Per Inch (tpi):                    |
| Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Between 99.0 degrees and 101.0 degrees<br>Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | 28   |
| Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Surface Finish:<br>32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br>   | Countersink Angle:                             |
| 32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | 32.0 microinches threads<br>Material:<br>Iron alloy 660<br>Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Between 99.0 degrees and 101.0 degrees         |
| Material:Iron alloy 660Material Specification:Ams5737 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, ty2, cl2 federal specification single treatment responseThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:   | Material:Iron alloy 660Material Specification:Ams5737 assn standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, ty2, cl2 federal specification single treatment responseThread Series Designator:UnjfShelf Life:N/aUnit Of Measure:Demilitarization:   | Surface Finish:                                |
| Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:  | Iron alloy 660 Material Specification: Ams5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:  | 32.0 microinches threads                       |
| Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  | Material Specification:<br>Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  | Material:                                      |
| Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Ams5737 assn standard single material response<br>Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Iron alloy 660                                 |
| Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Material Specification:                        |
| Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Surface Treatment:<br>Cadmium and chromate<br>Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Ams5737 assn standard single material response |
| Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Surface Treatment Specification:<br>Qq-p-416, ty2, cl2 federal specification single treatment response<br>Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   |  |
| Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:   | Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:   | Cadmium and chromate                           |
| Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:   | Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:   | Surface Treatment Specification:               |
| Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | Thread Series Designator:<br>Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:   | -  |
| Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  | Unjf<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  |  |
| Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  | Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:  | -  |
| N/a<br>Unit Of Measure:<br><br>Demilitarization:   | N/a<br>Unit Of Measure:<br><br>Demilitarization:   | -  |
| Unit Of Measure:<br><br>Demilitarization:  | Unit Of Measure:<br><br>Demilitarization:  |  |
| <br>Demilitarization:  | <br>Demilitarization:  |  |
|  |  |  |
|  |  | Demilitarization:                              |
| No   |  |  |
|  |  |  |

## NSN 5305-01-190-4591

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

