Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-190-7549

Tł	nread Class:
2a	a
Th	nread Direction:
Ri	ight-hand
Tł	nread Length:
Be	etween 0.151 inches and 0.161 inches
Fa	astener Length:
Be	etween 0.442 inches and 0.452 inches
He	ead Style:
Pa	an
He	ead Diameter:
Be	etween 0.256 inches and 0.270 inches
He	ead Height:
Be	etween 0.087 inches and 0.097 inches
Fi	rst Diameter From Head:
Be	etween 0.093 inches and 0.098 inches
Di	stance From Largest Bearing Surface Of Head To End Of First Diameter:
Be	etween 0.281 inches and 0.301 inches
In	ternal Drive Style:
Cr	ross recess type 1
Tł	nread Diameter:
0.	138 inches
Tł	nready Qty Per Inch (tpi):
32	2
E	xternally Relieved Body Diameter Quantity:
1	
M	aterial:
St	eel comp 302 or steel comp 303 or steel comp 304 or steel comp 305
M	aterial Specification:
66	federal standard all material responses or aisi assn standard all material responses
Sı	urface Treatment:
Pa	assivate
Sı	urface Treatment Specification:
Q	q-p-35 federal specification single treatment response
Tł	nread Series Designator:
Ur	nc
Sł	helf Life:
N/	/a
Uı	nit Of Measure:
De	emilitarization:
No	0

## NSN 5305-01-190-7549

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

