

View Online at <https://aerobasegroup.com/nsn/5305-01-190-7556>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.454 inches and 0.521 inches

**Fastener Length:**

Between 1.464 inches and 1.511 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.578 inches and 0.634 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.990 inches and 1.010 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Navy special project

**Special Features:**

Drive ribbed

**Material:**

Steel comp h11

**Material Specification:**

Ams6487 assn standard single material response

**Surface Treatment:**

Cadmium or cadmium and chromate

**Surface Treatment Specification:**

Nas672 assn standard 1st treatment response or mil-c-8837, ty2, cl2 military specification 2nd treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.