## NSN 5305-01-191-0388

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-191-0388
Thread Class:
Ba
Thread Direction:
Right-hand
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 0.949 inches and 0.979 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.244 inches and 0.279 inches
nternal Drive Style:
High-torque
Thread Diameter:
0.138 inches
Гhready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 24.0 rockwell c and 35.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Navy special project
Screw Material:
ron alloy 660
Screw Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams 5737 assn standard single
material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Γhread Series Designator:
Jnjc
Specification Data:
30205-nas1221 professional/industrial association standard
Shelf Life:
N/a

--

Unit Of Measure:

## NSN 5305-01-191-0388

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0