

View Online at <https://aerobasegroup.com/nsn/5305-01-191-0413>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.378 inches and 0.428 inches

**Fastener Length:**

Between 0.575 inches and 0.605 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.350 inches and 0.399 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.177 inches and 0.197 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Internal drive ribbed

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1581 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0