

View Online at <https://aerobasegroup.com/nsn/5305-01-191-2454>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.690 inches and 2.500 inches

**Fastener Length:**

Between 2.440 inches and 2.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.921 inches and 0.938 inches

**Head Height:**

Between 0.616 inches and 0.625 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.625 inches

**Width Across Flats:**

Between 0.500 inches and 0.505 inches

**Thready Qty Per Inch (tpi):**

11

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Minimum Yield Strength:**

30000 pounds per square inch

**Material:**

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

4 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0