NSN 5305-01-191-3095

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-191-3095 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.173 inches and 0.203 inches **Fastener Length:** Between 0.547 inches and 0.577 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.207 inches and 0.225 inches First Diameter From Head: Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.258 inches and 0.338 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 81.0 degrees and 83.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 or steel comp 303se **Material Specification:** Astma581 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-191-3095

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0