NSN 5305-01-191-4594

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-191-4594 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.506 inches and 0.556 inches **Fastener Length:** Between 1.454 inches and 1.484 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.429 inches and 0.477 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Mil-c-83488, type 2, class 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A003b0

NSN 5305-01-191-4594

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-83488 spec.