## NSN 5305-01-191-6268

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-191-6268 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.402 inches **Fastener Length:** Between 0.987 inches and 1.017 inches **Head Style:** Flat countersunk undercut **Head Diameter:** 0.531 inches **Head Height:** Between 0.057 inches and 0.059 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** Navy special project **Screw Material:** Steel **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Special Features:** Concentric hole 0.1596 in. Min dia, 0.1675 in. Maximum dia, 0.10 in. Thd diameter 32 thds per in., countersunk 90 degrees 0.156 in. Min dia, 0.187 in. Maximum diameter 0.353 in. Min; 0.425 in. Maximum length **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## **NSN 5305-01-191-6268** Machine Screw - Page 2 of 2



Fiig:

A500d0