NSN 5305-01-191-7496

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-191-7496 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.410 inches and 0.443 inches **Fastener Length:** Between 0.765 inches and 0.812 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.502 inches and 0.507 inches **Head Height:** Between 0.065 inches and 0.067 inches **Shoulder Diameter:** 0.2646 inches first shoulder and 0.2651 inches first shoulder **Shoulder Length:** 0.237 inches first shoulder and 0.255 inches first shoulder **Internal Drive Style:** High-torque Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one o ring Material: Stainless steel **Material Specification:** St7-251 fscm 76301 mfr ref single material response **Thread Series Designator:** Unjf Shelf Life:

N/a **Unit Of Measure:**--

NSN 5305-01-191-7496

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0